

VKF-Anwendungen Typ E - SICUROFLAM®

Festverglasungen

Nr.	Typ	Profilsystem	Totalstärke mm	H-max/mm	A-max/m2	Lichttrans- mission %	Schalldämm- wert dB	U-Wert W/m2/K	Gewicht	Ausführung Glas/mm	SZR	Gas	Aussenglas (Deckglas)	VKF- Anw.
1	Mono E30/6	Jansen Eco 50	6	3000	2,6	92	31	5,8	15	Sicuroflam 6	0	0	0	13744
2	Mono E30/8	Jansen Eco 50	8	2620	3,1	90	32	5,8	20	Sicuroflam 8	0	0	0	13747
3	Mono E30/10	Jansen Eco 50	10							Sicuroflam 10				geprüft
4	Mono E30/12	Jansen Eco 50	12	3000	4,3	88	35	5,8	30	Sicuroflam 12	0	0	0	13745
5	Iso E30/24	Jansen Eco 50	24	2210	2,21	84	32	3,0	30	2 x Sicurofl 6	12	Luft	6 Sicuroflam	13748
6	Iso E30/24 1,1	Jansen Eco 50	24	2210	2,21	84	32	1,2	30	2 x Sicurofl 6	12	Argon	6 Sicuroflam LE	13748

Rahmenlos (ohne Vertikalprofil)

7	E30/12 Line	eigenes	12	3000	4,4	88	35	5,8	30	Sicuroflam Line	0	0	0	14300
---	-------------	---------	----	------	-----	----	----	-----	----	-----------------	---	---	---	-------

Liste VKF-Anwendungen Typ E- SICUROFLAM® (06-2011)